



YYWW JM8-CF15-5600

噴印週期及料號

LED SCHEMATIC:
LEFT LED1:
LEFT LED2: GREEN
RIGHT LED1:
RIGHT LED2: GREEN

L4 + — L3 -

L2 + — L1 -

PART NUMBER:
JM8-C F 1 5-5 6 0 0

SHELL CODE
F:W/TOP SPRING,W/O LOGO
1-Housing PBT
LED CODE
LEFT LED1: GREEN
LEFT LED2: GREEN
RIGHT LED1: GREEN
RIGHT LED2: GREEN

DIM CODE
Contact PIN DIM A :3.18
LED PIN DIM B :3.18

PLATING CODE
5-GOLD PLATED 15u"

NOTES:
1.MATERIAL:
HOUSING:HIGH TEMP.THERMOPLASTIC, PBT BLACK,UL 94V-0
CONTACT:PHOSPHOR BRONZE,T=0.35mm
SHELL:BRASS,T=0.25mm
2.FINISH:
CONTACT:50u"MIN. NICKEL UNDERPLATING ALL AREA,100u"MIN.
TIN ON SOLDERTAILS,GOLD PLATING ON CONTACT AREA.
3.OPERATING TEMPERATURE:-40°C~+85°C.
4-JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F

FUCHENG

PCB LAYOUT TOLERANCE:±0.05

REV. A	ECN. NO. NEW	DRAWN YongDe	DATE 06/25/2015	EC.content
<p>④:QUALITY CONTROL ITEM</p> <p>APPROVED</p> <p>CHECKED</p> <p>DRAWN</p>				
GENERAL TOLERANCE		PART NO.: JM8-CF15-5600		
X:±0.38		TITLE:RJ45 2x8 JACK		
Y:±0.25		W/ LED & SHELL T/H		
Z:±0.13		SCALE:1:1		
UNIT: mm		SHEET: 1/1		
REV: A		REV: A		