


修改图档与实物一致

Plated G/F Selective Contact Area
Electrical:
Current Rating :0.5mA AC/DC max.
Voltage Rating :125V AC/DC
Ambient Temperature Range : -20°C~+60°C
Storage Temperature Range : -40°C~+70°C
Ambient Humidity Range :95% R.H. Max.
Contact Resistance:100m ohm.
Insulation Resistance:100M min./500VDC
Mating Cycles:5,000 Insertions
Temperature:260C ±5°

PLATING:

Plaided w/ r selective conduct Alcu
Electrical:

Mating Cycles: 5,000 Insertions
Temperature: 260°C $\pm$ 5°

■ SMT SOLDER AREA

IN THE LAYOUT SPACE OF THE PRODUCTS

GENERAL TOLERANCE ± 0.05

MILLIMETERS		INCH		UNITS		MM	
$X^{\circ} \pm Z^{\circ}$		$X^{\circ} \pm$		MATL			
$.X \pm 0.30$		$.XX \pm$		SEE NOTES			
$.XX \pm 0.20$		$.XXX \pm$		FINISH			
$.XXX \pm 0.10$		$.XXXX \pm$		SEE NOTES			
THESE DIMENSIONS AND SPECIFICATIONS ARE THE PROPERTY OF Dong Guan Jin Bi Lai Electronic Co., Ltd.				COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF Dong Guan Jin Bi Lai Electronic Co., Ltd.			
QTY				SEE NOTES			
APPD: WEI				PART NUMBER: 102030942			
CHKD:				TITLE: MICRO-SIM PUSH/PUSH 6PIN 1.35H (带薄片) 客户图			
DR: Yanq				DWG NO.: C-102030942-00			
				SCALE 1:1		SHEET 1/2	
						REV. A1	